

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 08/05/2014 Revision date: 08/05/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : PENRAY OIL SYSTEM CLEANER

Product code : 7512

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Motor flush.

1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc. 440 Denniston Ct. Wheeling, IL 60090 T (800) 373-6729 rotto@penray.com

1.4. Emergency telephone number

Emergency number : (800) 373-6729

CHEMTREC (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 3 Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposure 3 Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS07

Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US)

Keep away from heat/sparks/open flames/hot surfaces.— No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

08/05/2014 EN (English) Page 1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kerosene, petroleum	(CAS No) 8008-20-6	60 - 100	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Naphthalene	(CAS No) 91-20-3	0.1 - 1	Acute Tox. 4 (Oral) Carc. 2

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.

Symptoms/injuries after skin contact

: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact

May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

5.3. Advice for firefighters

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment

 Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

08/05/2014 EN (English) 2/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a wellventilated area

Hygiene measures Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

Control parameters

Kerosene, petroleum (8008-20-6)		
USA ACGIH	ACGIH TWA (mg/m³)	200 mg/m ³
Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Exposure controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal protective equipment

: Avoid all unnecessary exposure.

Hand protection

Wear chemically resistant protective gloves.

Eye protection

Safety glasses or goggles are recommended when using product.

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

Maintain levels below Community environmental protection thresholds

Other information

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid. Appearance : Clear. Color Red. Odor Solvent.

Odor threshold : No data available.

Ha Neutral

Relative evaporation rate (butylacetate=1) : No data available. Melting point No data available. Freezing point No data available.

Boiling point : 182 - 288 °C (360 - 550 °F) Flash point 49 - 88 °C (120 - 190 °F) Self ignition temperature : ~ 254 °C (~ 489 °F) Decomposition temperature : No data available. Flammability (solid, gas) : Flammable.

: 1 - 10 mm Hg @ 38 °C (100 °F) Vapor pressure

08/05/2014 EN (English) 3/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Relative vapor density at 20 °C : 4-5 Relative density : ~ 0.8 Solubility : Negligible. Log Pow : No data available. Log Kow : No data available.

Viscosity, kinematic : 1.3 - 2.1 @ 50 °C (122 °F)

Viscosity, dynamic : No data available.

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : 0.7 - 5 vol %

9.2. Other information

VOC content : 10 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

7512		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	No data available.	

Kerosene, petroleum (8008-20-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	> 5.28 mg/l/4h	

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg
LC50 inhalation rat	>340 mg/m³/1h
LC50 inhalation rat	>0.4 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Suspected of causing cancer.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Based on available data, the classification criteria are not met.

08/05/2014 EN (English) 4/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory

tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

7512		
	Persistence and degradability	Not established

12.3. Bioaccumulative potential

7512	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No. : UN1223

14.2. UN proper shipping name

Proper Shipping Name : Kerosene

Department of Transportation Hazard Classes

Hazard labels



Packing group : III

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

08/05/2014 EN (English) 5/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Naphthalene (91-20-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %


15.2. US State regulations

7512	
State or local regulations	This product contains a chemical known to the State of California to cause cancer.

SECTION 16: Other information

Indication of changes: None.Date of issue: 08/05/2014Other information: None.

NFPA health hazard : 2
NFPA fire hazard : 2
NFPA reactivity : 1



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

