SAFETY DATA SHEET


1. Identification

Product number	1000029860
Product identifier	16 OZ CLAIRE WB MANGO AIR FRSHNR LB 12PK
Company information	CLAIRE MANUFACTURING COMPANY 1005 S. WESTGATE DRIVE ADDISON, IL 60101 United States
Company phone	General Assistance 800-252-4731
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	AIR FRESHENER
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards		
Health hazards		
OSHA defined hazards		

Label elements



Category 1



Signal word	Danger
Hazard statement	Extremely flammable aerosol.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
1,2-Propanediol		57-55-6	2.5 - 10
Propane		74-98-6	2.5 - 10
Other components below	reportable levels		60 - 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR		,	
Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	

Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
	1000 ppm		
US. Workplace Environme	ntal Exposure Level (WEEL) Guides		
Components	Туре	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.
•	No biological exposure limits noted for	•	be used Ventilation rates
ological limit values propriate engineering ntrols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels	ures, local exhaust ventilation ommended exposure limits.
propriate engineering ntrols dividual protection measures	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent	ures, local exhaust ventilation ommended exposure limits.
propriate engineering ntrols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent	ures, local exhaust ventilation ommended exposure limits.
propriate engineering ntrols dividual protection measures	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent	ures, local exhaust ventilation ommended exposure limits.
propriate engineering ntrols dividual protection measures Eye/face protection	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent (or goggles).	ures, local exhaust ventilatic ommended exposure limits. s to an acceptable level.
propriate engineering ntrols dividual protection measures Eye/face protection Skin protection	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm Wear safety glasses with side shields Wear appropriate chemical resistant	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent (or goggles).	ures, local exhaust ventilatic ommended exposure limits. s to an acceptable level.
propriate engineering ntrols dividual protection measures Eye/face protection Skin protection Hand protection	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm Wear safety glasses with side shields Wear appropriate chemical resistant supplier.	air changes per hour) should oplicable, use process enclose ain airborne levels below reco shed, maintain airborne levels ent (or goggles). gloves. Suitable gloves can be	ures, local exhaust ventilation ommended exposure limits. Is to an acceptable level.
propriate engineering ntrols dividual protection measures Eye/face protection Skin protection Hand protection Other	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi s, such as personal protective equipm Wear safety glasses with side shields Wear appropriate chemical resistant supplier. Wear suitable protective clothing. If permissible levels are exceeded us	air changes per hour) should oplicable, use process enclosi ain airborne levels below reco shed, maintain airborne levels ent (or goggles). gloves. Suitable gloves can be e NIOSH mechanical filter / or	ures, local exhaust ventilation ommended exposure limits. Is to an acceptable level.

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.

Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.881 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

nouonny	
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Components	Species	Test Results
1,2-Propanediol (CAS 57-55-	-6)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral		
LD50	Guinea pig	19700 mg/kg
	Mouse	24900 mg/kg
	Rat	22000 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	т	est Results
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1	237 mg/l, 120 Minutes
		5	2 %, 120 Minutes
	Rat	1	355 mg/l
		6	58 mg/l/4h
* Estimates for product may	be based on add	litional component data not shown.	
Skin corrosion/irritation	Prolonged sk	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contac	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization	on		
Respiratory sensitization	Not a respirat	tory sensitizer.	
Skin sensitization	This product	is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overal Not listed. OSHA Specifically Regular Not regulated. US. National Toxicology P Not listed.	ed Substances	(29 CFR 1910.1001-1050)	
Reproductive toxicity	This product i	is not expected to cause reproductive or de	evelopmental effects.
Specific target organ toxicity - single exposure	Not classified	l.	
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
12. Ecological informatio	n		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Components		Species	Test Results
1,2-Propanediol (CAS 57-55	-6)		
Aquatic			
Crustacea	EC50	Daphnia	10000.0001 mg/L, 48 Hours
		Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)) 710 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)			
1,2-Propanediol	-0.92		
Butane	2.89		
Propane	2.36		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	• •	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IME	G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	
	Marine pollutant	No.
	EmS	F-D, S-U
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Packaging ExceptionsLTD QTYTransport in bulk according to
Annex II of MARPOL 73/78 and
the IBC CodeNot applicable.

FLAMMABLE GAS 2 IATA; IMDG

DOT

15. Regulatory information This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. Superfund Amendments and Reauthorization Act of 1986 (SARA) **Hazard categories** Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

1,2-Propanediol (CAS 57-55-6) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2-Propanediol (CAS 57-55-6) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988		
Acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988		
Ethylene Oxide (CAS 75-21-8)	Listed: July 1, 1987		
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988		
US - California Proposition 65 - CRT: Listed date/Developmental toxin			
Ethylene Oxide (CAS 75-21-8)	Listed: August 7, 2009		
US - California Proposition 65 - CRT: Liste	d date/Female reproductive toxin		
Ethylene Oxide (CAS 75-21-8)	Listed: February 27, 1987		
US - California Proposition 65 - CRT: Liste	d date/Male reproductive toxin		
Ethylene Oxide (CAS 75-21-8)	Listed: August 7, 2009		

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-25-2016
Version #	01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.