claire

SAFETY DATA SHEET

1. Identification

Product number	1000026131
Product identifier	DUST MOP TREATMENT
Company information	Claire Manufacturing Co. 1005 S. Westgate Drive Addison, IL 60101 United States
Company phone	General Assistance 1-630-543-7600
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	Cleaner
Recommended restrictions	None known.
2. Hazard(s) identification	

Physical hazards Health hazards **Environmental hazards OSHA** defined hazards

Label elements

Flammable aerosols Aspiration hazard Not classified. Not classified.



Category 1 Category 1

	\mathbf{v} \mathbf{v}
Signal word	Danger
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
Butane		106-97-8	2.5 - 10
Propane		74-98-6	1 - 2.5
Other components below reportable	levels		60 - 80

mponents below reportable levels Other

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

propriate engineering introlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.lividual protection measures, such as personal protective equipment Face shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherUvear suitable protective clothing.Respiratory protection air-supplied respirator.If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazards metal hygiene msiderationsWear appropriate thermal protective clothing, when necessary.When using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Components	Туре	Value		
US. ACGIH Threshold Limit Values Components Type Value Butane (CAS 106-97-8) STEL 1000 ppm US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm Propane (CAS 74-98-6) TWA 1900 mg/m3 1000 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm Objicial limit values propriate engineering ntrols No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventiling or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels below recommended level. Butane protection Face shield is recommended. Wear safety glasses with side shields (or goggles). Hand protection Wear appropriate chemical resistant gloves. Skin protection If permissible protective clothing. Respiratory protection If permissible are exceeded use NIOSH mechanical filter / organic vapor	Propane (CAS 74-98-6)	PEL	1800 mg/m3		
ComponentsTypeValueButane (CAS 106-97-8)STEL1000 ppmUS. NIOSH: Pocket Guide to Chemical Hazards ComponentsTypeValueButane (CAS 106-97-8)TWA1900 mg/m3 800 ppmPropane (CAS 74-98-6)TWA1900 mg/m3 1000 ppmPropane (CAS 74-98-6)TWA1800 mg/m3 1000 ppmPropriate engineering ntrolsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.Ividual protection Hand protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazards meral hygiene misdlerationsWear appropriate thermal protective clothing, when necessary.			1000 ppm		
Butane (CAS 106-97-8) STEL 1000 ppm US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm propriate engineering introls No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level. Ividual protection measures, such as personal protective equipment Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles). Hand protection Wear appropriate chemical resistant gloves. Skin protection Wear suitable protective clothing. Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. meral hygiene misiderations When using do not smoke. Always observe good personal hygiene measures, such as wash after handing the material and before eating, drinking, and/					
US. NOSH: Pocket Guide to Chemical Hazards Components Type Value Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm propriate engineering introls No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilat or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level. Itividual protection measures, such as personal protective equipment Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles). Hand protection Wear appropriate chemical resistant gloves. Skin protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. meral hygiene msiderations When using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	Components	Туре	Value		
ComponentsTypeValueButane (CAS 106-97-8)TWA1900 mg/m3 800 ppmPropane (CAS 74-98-6)TWA1800 mg/m3 1000 ppmpropriate engineering ntrolsNo biological exposure limits noted for the ingredient(s).good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.Itividual protection Mean protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection Respiratory protectionIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazards meral hygiene msiderationsWear appropriate thermal protective clothing, when necessary.Menu using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Butane (CAS 106-97-8)	STEL	1000 ppm		
Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm ological limit values propriate engineering ntrols No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level. Bividual protection measures, skin protection Such as personal protective equipment Face shield is recommended. Wear safety glasses with side shields (or goggles). Wear appropriate chemical resistant gloves. Skin protection Other Wear suitable protective clothing. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. when using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	US. NIOSH: Pocket Guide	to Chemical Hazards			
Propane (CAS 74-98-6)TWA800 ppm 1800 mg/m3 1000 ppmological limit valuesNo biological exposure limits noted for the ingredient(s).opropriate engineering ntrolsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila cor other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.dividual protection measures, such as personal protective equipment Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.when using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Components	Туре	Value		
Propane (CAS 74-98-6)TWA1800 mg/m3 1000 ppmDological limit valuesNo biological exposure limits noted for the ingredient(s).propriate engineering ntrolsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.lividual protection measures, such as personal protective equipment Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.neral hygiene msiderationsWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Butane (CAS 106-97-8)	TWA	1900 mg/m3		
1000 ppmological limit values propriate engineering ntrolsNo biological exposure limits noted for the ingredient(s).Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.lividual protection measures, such as personal protective equipment Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherIf permissible protective clothing. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazards msiderationsWear appropriate thermal protective clothing, when necessary.meral hygiene msiderationsWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor			800 ppm		
blogical limit valuesNo biological exposure limits noted for the ingredient(s).propriate engineering introlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.lividual protection measures, such as personal protective equipment Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherWear suitable protective clothing.Respiratory protection meral hazardsUser appropriate thermal protective clothing, when necessary.Wear appropriate thermal protective clothing, when necessary.Wen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Propane (CAS 74-98-6)	TWA	1800 mg/m3		
propriate engineering introlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.lividual protection measures, such as personal protective equipment Face shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherUvear suitable protective clothing.Respiratory protection air-supplied respirator.If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazards metal hygiene msiderationsWear appropriate thermal protective clothing, when necessary.When using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash wor			1000 ppm		
Introlsshould be matched to conditions. If applicable, use process enclosures, local exhaust ventila or other engineering controls to maintain airborne levels below recommended exposure limit exposure limits have not been established, maintain airborne levels to an acceptable level.Ividual protection measures, such as personal protective equipment Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protection OtherWear appropriate chemical resistant gloves.Skin protection OtherWear suitable protective clothing. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.meral hygiene nsiderationsWean using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash worl	logical limit values	No biological exposure limits noted	for the ingredient(s).		
Eye/face protectionFace shield is recommended. Wear safety glasses with side shields (or goggles).Hand protectionWear appropriate chemical resistant gloves.Skin protectionWear suitable protective clothing.OtherWear suitable protective clothing.Respiratory protectionIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.meral hygiene nsiderationsWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work		Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.			
Hand protection Wear appropriate chemical resistant gloves. Skin protection Wear suitable protective clothing. Other Wear suitable protective clothing. Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. neral hygiene insiderations When using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	ividual protection measure	s, such as personal protective equipr	nent		
Skin protection Wear suitable protective clothing. Other Wear suitable protective clothing. Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. neral hygiene When using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).			
OtherWear suitable protective clothing.Respiratory protectionIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.Ineral hygiene nsiderationsWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	Hand protection	Wear appropriate chemical resistant	Wear appropriate chemical resistant gloves.		
Respiratory protectionIf permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or a air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.Ineral hygiene nsiderationsWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	Skin protection				
air-supplied respirator.Thermal hazardsWear appropriate thermal protective clothing, when necessary.neral hygieneWhen using do not smoke. Always observe good personal hygiene measures, such as wash after handling the material and before eating, drinking, and/or smoking. Routinely wash work	Other	Wear suitable protective clothing.			
neral hygieneWhen using do not smoke. Always observe good personal hygiene measures, such as washnsiderationsafter handling the material and before eating, drinking, and/or smoking. Routinely wash work	Respiratory protection		If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
nsiderations after handling the material and before eating, drinking, and/or smoking. Routinely wash wor	Thermal hazards	Wear appropriate thermal protective	Wear appropriate thermal protective clothing, when necessary.		
		When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

9. Physical and chemical properties

-	-
Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	191.73 °F (88.74 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.

Explosive limit - upper (%)	Not available.
Vapor pressure	18.41 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	392 °F (200 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.678 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Acute toxicity	Intertoxicity May be latar if swallowed and enters all ways.	
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Distillates (Petroleum), Hyd	drotreated Light (CAS 64742-47-8)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours

Components	Species	i	Test Results	
<i>Oral</i> LD50	Rat		> 5000 mg/kg	
Propane (CAS 74-98-6)				
Acute				
Inhalation				
LC50	Mouse		1237 mg/l, 120 Minutes	
			52 %, 120 Minutes	
	Rat		1355 mg/l	
			658 mg/l/4h	
* Estimates for product may	be based on a	additional component data not shown.		
Skin corrosion/irritation	Prolonged	skin contact may cause temporary irritat	tion.	
Serious eye damage/eye irritation	Direct con	tact with eyes may cause temporary irrita	ation.	
Respiratory or skin sensitizati	ion			
Respiratory sensitization	Not availa	ble.		
Skin sensitization	This produ	ict is not expected to cause skin sensitization	ation.	
Germ cell mutagenicity		vailable to indicate product or any compo or genotoxic.	onents present at greater than 0.1% are	
Carcinogenicity	This produ	ict is not considered to be a carcinogen b	by IARC, ACGIH, NTP, or OSHA.	
OSHA Specifically Regula Not listed.	ited Substanc	es (29 CFR 1910.1001-1050)		
Reproductive toxicity	This produ	ict is not expected to cause reproductive	or developmental effects.	
Specific target organ toxicity - single exposure	 Not classif 	Not classified.		
Specific target organ toxicity - repeated exposure	 Not classif 	fied.		
Aspiration hazard	May be fat	tal if swallowed and enters airways.		
12. Ecological information	on			
Ecotoxicity			zardous. However, this does not exclude the armful or damaging effect on the environment.	
Components		Species	Test Results	
Distillates (Petroleum), Hyd Aquatic	rotreated Light	(CAS 64742-47-8)		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
* Estimates for product may	/ be based on a	additional component data not shown.		
Persistence and degradability	No data is	available on the degradability of this pro	duct.	
Bioaccumulative potential	No data av	vailable.		
Partition coefficient n-oct	anol / water (l	og Kow)		
Butane Propane		2.89 2.36		
Mobility in soil	No data av	No data available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal considerati	ons			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.			
	WILL IOCAI/I	regional/national/international regulations	b .	
Local disposal regulations		accordance with all applicable regulation		

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.







IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

Hazard categories

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-29-2015
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.