# CPC

# SAFETY DATA SHEET

### 1. Identification

Product number 1000011442

Product identifier TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

Company information CPC

1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States

Company phone General Assistance 800-327-1835

Emergency telephone US 1-866-836-8855 Emergency telephone outside 1-952-852-4646

US

Version # 01

Recommended use Not available.
Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazardsGases under pressureCompressed gasHealth hazardsSerious eye damage/eye irritationCategory 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Wash thoroughly after handling. Wear eye protection/face protection.

**Response** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Storage** Protect from sunlight. Store in a well-ventilated place.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Silica, amorphous		7631-86-9	10 - 20
Ethyltriacetoxysilane		17689-77-9	2.5 - 10
Methyltriacetoxysilane		4253-34-3	2.5 - 10
Other components below reportable levels			60 - 80

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

**Eve contact** 

Ingestion

\_,.......

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or

poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods
General fire hazards

Cool containers exposed to flames with water until well after the fire is out.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. NIOSH: Pocket Guide to Chemical Hazards
Components
Type

Silica, amorphous (CAS TWA 6 mg/m3

7631-86-9)

**Biological limit values**No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Value

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Gas.

Form Aerosol. Compressed gas.

Color Not available.

Odor Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 212.0 °F (100.0 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower No

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

Specific gravity 1.007 @25C estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**Material is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact**No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

## Information on toxicological effects

**Acute toxicity** 

Components Species Test Results

Ethyltriacetoxysilane (CAS 17689-77-9)

Acute Oral

LD50 Rat 1460 mg/kg

2.1 ml/kg

Methyltriacetoxysilane (CAS 4253-34-3)

Acute Oral

LD50 Rat 1550 mg/kg

1.58 ml/kg

Silica, amorphous (CAS 7631-86-9)

Acute Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 2.08 mg/l, 4 Hours

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

**Species Test Results** Components Oral LD50 Mouse > 3160 mg/kg Rat > 3300 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Prolonged inhalation may be harmful.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, amorphous (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity repeated exposure

**Chronic effects** 

Not classified.

**Aspiration hazard** Not likely, due to the form of the product.

12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
TERAND-11407 RTV	SILICONE GASKE	T MAKER - BLUE		
Aquatic				
Algae	IC50	Algae	3384.6155 mg/L, 72 Hours estimated	
Crustacea	EC50	Daphnia	58461.5391 mg/L, 48 Hours estimated	
Components		Species	Test Results	
Silica, amorphous (CA	S 7631-86-9)			
Aquatic				
Algae	IC50	Algae	440 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	7600 mg/L, 48 Hours	

This product is not expected to cause reproductive or developmental effects.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

## 14. Transport information

DOT

UN1950 **UN number** 

**UN** proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group Special precautions for user Not available.

N82 Special provisions Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

**UN number** UN1950

Aerosols, flammable **UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Cargo aircraft only

Allowed with restrictions. Allowed with restrictions.

**Packaging Exceptions** LTD QTY

**IMDG** 

UN1950 **UN number** UN proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. **EmS** F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE



IATA; IMDG



**General information** 

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

### **US state regulations**

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### **US. Massachusetts RTK - Substance List**

Silica, amorphous (CAS 7631-86-9)

#### US. New Jersey Worker and Community Right-to-Know Act

Not listed

## US. Pennsylvania Worker and Community Right-to-Know Law

Silica, amorphous (CAS 7631-86-9)

#### **US. Rhode Island RTK**

Not regulated.

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region

oddini y(3) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Inventory name

Issue date 10-02-2018

Version # 01

United States & Puerto Rico

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Product name: TERAND-11407 RTV SILICONE GASKET MAKER - BLUE

Yes

On inventory (yes/no)\*