# SAFETY DATA SHEET

#### 1. Identification

**Product number** 1000001315

**Product identifier** 15 OZ TERAND MTL PLSH OIL-BASED LEMON

07-27-2016 **Revision date** 

CPC **Company information** 

1005 S. Westgate Drive

Addison, IL 60101 United States

General Assistance 800-327-1835 Company phone

**Emergency telephone US** 1-866-836-8855 **Emergency telephone outside** 

1-952-852-4646

Version # 15

12-06-2015 Supersedes date Recommended use **CLEANER** Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Health hazards Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic

skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

**Precautionary statement** 

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

> flame or other ignition source. Pressurized container: Do not pierce or burn, even after use, Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face

protection. Wear protective gloves.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting, If on skin: Wash Response

with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash

contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information None.

Product name: 15 OZ TERAND MTL PLSH OIL-BASED LEMON Product #: 1000001315 Version #: 15 Revision date: 07-27-2016 Issue date: 12-30-2014

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
White Mineral Oil (petroleum)		8042-47-5	20 - 40
Acetone		67-64-1	10 - 20
Propane		74-98-6	10 - 20
Methyl Acetate		79-20-9	2.5 - 10
Citral		5392-40-5	0.1 - 1
Orange Terpenes		68647-72-3	0.1 - 1
Other components below reportal	ole levels		0.1 - 1

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders. Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth, Do not induce vomiting, If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed **General information**  Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Combustible.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

IIS OSHA Table 7-11 imits for Air Contaminants (29 CEP 1910 1000)

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

Methyl Acetate (CAS   PEL   1000 ppm   610 mg/m3   79-20-9)   200 ppm   20	Components	Туре	Value	
Methyl Acetate (CAS 74-98-6) PEL 610 mg/m3 79-20-9) 200 ppm	Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
79-20-9) 200 ppm Propane (CAS 74-98-6) PEL 1800 mg/m3 1000 ppm  US. ACGIH Threshold Limit Values Components Type Value Form  Acetone (CAS 67-64-1) STEL 500 ppm TWA 250 ppm Inhalable fraction and vapor.  Methyl Acetate (CAS S392-40-5) TWA 250 ppm Inhalable fraction and vapor.  WELS. NIOSH: Pocket Guide to Chemical Hazards Components Type Value  Acetone (CAS 67-64-1) TWA 590 mg/m3 250 ppm Methyl Acetate (CAS STEL 760 mg/m3 79-20-9) TWA 590 ppm  TWA 590 ppm  TWA 610 mg/m3 200 ppm  Propane (CAS 74-98-6) TWA 1800 mg/m3			1000 ppm	
Propane (CAS 74-98-6)         PEL         1800 mg/m3 1000 ppm           US. ACGIH Threshold Limit Values         Type         Value         Form           Acetone (CAS 67-64-1)         STEL         500 ppm           Acetone (CAS 5392-40-5)         TWA         250 ppm           Citral (CAS 5392-40-5)         TWA         5 ppm         Inhalable fraction and vapor.           Methyl Acetate (CAS 79-20-9)         TWA         250 ppm           US. NIOSH: Pocket Guide to Chemical Hazards         Type         Value           Acetone (CAS 67-64-1)         TWA         590 mg/m3 250 ppm           Methyl Acetate (CAS 76-64-1)         TWA         590 mg/m3 250 ppm           Methyl Acetate (CAS 76-64-1)         TWA         610 mg/m3 200 ppm           Propane (CAS 74-98-6)         TWA         1800 mg/m3	Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3	
US. ACGIH Threshold Limit Values Components  Type  Value Form  Acetone (CAS 67-64-1)  TWA  Citral (CAS 5392-40-5)  Methyl Acetate (CAS 79-20-9)  TWA  COMPONENTS  TWA  TWA  TWA  TWA  TWA  TWA  TWA  T			200 ppm	
Components         Type         Value         Form           Acetone (CAS 67-64-1)         STEL         500 ppm           TWA         250 ppm         Inhalable fraction and vapor.           Citral (CAS 5392-40-5)         TWA         5 ppm         Inhalable fraction and vapor.           Methyl Acetate (CAS 79-20-9)         STEL         250 ppm         250 ppm           US. NIOSH: Pocket Guide to Chemical Hazards         Components         Type         Value           Acetone (CAS 67-64-1)         TWA         590 mg/m3         250 ppm           Methyl Acetate (CAS 79-99)         STEL         760 mg/m3         250 ppm           TWA         610 mg/m3         200 ppm           Propane (CAS 74-98-6)         TWA         1800 mg/m3	Propane (CAS 74-98-6)	PEL	•	
Acetone (CAS 67-64-1)  Acetone (CAS 67-64-1)  TWA  STEL  TWA  250 ppm  Inhalable fraction and vapor.  Methyl Acetate (CAS  TWA  STEL  250 ppm  TWA  200 ppm  US. NIOSH: Pocket Guide to Chemical Hazards  Components  Type  Value  Acetone (CAS 67-64-1)  TWA  S90 mg/m3  250 ppm  Methyl Acetate (CAS  STEL  760 mg/m3  79-20-9)  TWA  610 mg/m3  200 ppm  Propane (CAS 74-98-6)  TWA  1800 mg/m3	US. ACGIH Threshold Limit Valu	ies		
TWA 250 ppm Citral (CAS 5392-40-5) TWA 5 ppm Inhalable fraction and vapor.  Methyl Acetate (CAS 579-20-9) TWA 200 ppm  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value  Acetone (CAS 67-64-1) TWA 590 mg/m3 250 ppm  Methyl Acetate (CAS 579-20-9) TWA 250 ppm  TWA 590 mg/m3 250 ppm  TWA 610 mg/m3 200 ppm  Propane (CAS 74-98-6) TWA 1800 mg/m3	Components	Туре	Value	Form
Citral (CAS 5392-40-5)       TWA       5 ppm       Inhalable fraction and vapor.         Methyl Acetate (CAS 79-20-9)       STEL       250 ppm         TWA       200 ppm       TWA         US. NIOSH: Pocket Guide to Chemical Hazards       Components         Components       Type       Value         Acetone (CAS 67-64-1)       TWA       590 mg/m3 250 ppm         Methyl Acetate (CAS 76-64-1)       STEL       760 mg/m3 250 ppm         79-20-9)       TWA       610 mg/m3 200 ppm         Propane (CAS 74-98-6)       TWA       1800 mg/m3	Acetone (CAS 67-64-1)	STEL	500 ppm	
Methyl Acetate (CAS 74-98-6)  STEL 250 ppm  TWA 200 ppm  TWA 200 ppm  Value  TWA 590 mg/m3 250 ppm 760 mg/m3 250 ppm  TWA 610 mg/m3 200 ppm  Propane (CAS 74-98-6)  TWA 1800 mg/m3		TWA	250 ppm	
TWA 200 ppm  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value  Acetone (CAS 67-64-1) TWA 590 mg/m3 250 ppm  Methyl Acetate (CAS STEL 760 mg/m3 79-20-9)  TWA 610 mg/m3 200 ppm  Propane (CAS 74-98-6) TWA 1800 mg/m3	Citral (CAS 5392-40-5)	TWA	5 ppm	
US. NIOSH: Pocket Guide to Chemical Hazards Components  Type  Acetone (CAS 67-64-1)  TWA  590 mg/m3 250 ppm  Methyl Acetate (CAS 79-20-9)  TWA  590 mg/m3 250 ppm 760 mg/m3 250 ppm 610 mg/m3 200 ppm  Propane (CAS 74-98-6)  TWA  1800 mg/m3		STEL	250 ppm	·
Components         Type         Value           Acetone (CAS 67-64-1)         TWA         590 mg/m3           250 ppm         250 ppm           Methyl Acetate (CAS         STEL         760 mg/m3           79-20-9)         250 ppm           TWA         610 mg/m3           200 ppm           Propane (CAS 74-98-6)         TWA         1800 mg/m3		TWA	200 ppm	
Acetone (CAS 67-64-1)  TWA  590 mg/m3 250 ppm  Methyl Acetate (CAS 760 mg/m3 79-20-9)  250 ppm  TWA  610 mg/m3 200 ppm  Propane (CAS 74-98-6)  TWA  1800 mg/m3	US. NIOSH: Pocket Guide to Che	emical Hazards		
250 ppm Methyl Acetate (CAS STEL 760 mg/m3 79-20-9)  250 ppm 250 ppm TWA 610 mg/m3 200 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Components	Туре	Value	
Methyl Acetate (CAS STEL 760 mg/m3 79-20-9) 250 ppm TWA 610 mg/m3 200 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Acetone (CAS 67-64-1)	TWA	590 mg/m3	
Methyl Acetate (CAS STEL 760 mg/m3 79-20-9) 250 ppm TWA 610 mg/m3 200 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	,		250 ppm	
TWA 610 mg/m3 200 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3	
200 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3	,		250 ppm	
Propane (CAS 74-98-6) TWA 1800 mg/m3		TWA	610 mg/m3	
			200 ppm	
1000 ppm	Propane (CAS 74-98-6)	TWA	1800 mg/m3	
			1000 ppm	

Product name: 15 OZ TERAND MTL PLSH OIL-BASED LEMON

SDS US

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

#### **US ACGIH Threshold Limit Values: Skin designation**

Citral (CAS 5392-40-5) Can be absorbed through the skin.

Appropriate engineering

controls

Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** 

Physical state Gas. **Form** Aerosol. Not available. Color Not available. Odor Not available. **Odor threshold** Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

347.39 °F (175.21 °C) estimated

-156.0 °F (-104.4 °C) Propellant estimated Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

2.7 % estimated

(%)

Flammability limit - upper

13.4 % estimated

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

45 - 65 psig @70F estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

608.04 °F (320.02 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

Specific gravity 0.765 - 0.865 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause an allergic skin

Acute toxicity	May be fatal it swallowed and enters alrways. Narcotic effects. May cause an allergic skin reaction.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
<u>Acute</u>			
Dermal			
LD50	Guinea pig	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
	Rabbit	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral			
LD50	Rat	5800 mg/kg	
		2.2 ml/kg	
Citral (CAS 5392-40-5)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	2250 mg/kg	
	Rat	> 2000 mg/kg, 24 Hours	
Oral			
LD50	Mouse	1424 mg/kg	

Product name: 15 OZ TERAND MTL PLSH OIL-BASED LEMON

SDS US

 Components
 Species
 Test Results

 Rat
 4895 mg/kg

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 7.5 mg/l, 6 Hours

> 4.6 mg/l, 4 Hours

Oral LD50

Rat > 5000 mg/kg

Methyl Acetate (CAS 79-20-9)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Inhalation

LC100 Rabbit 98.4 mg/l, 4 Hours

Oral

LD50 Rat 6482 mg/kg

Propane (CAS 74-98-6)

<u>Acute</u>

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l 658 mg/l/4h

White Mineral Oil (petroleum) (CAS 8042-47-5)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat 2.18 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**ACGIH** sensitization

Citral (CAS 5392-40-5) Dermal sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Acetone (CAS 67-64-	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Citral (CAS 5392-40-5	5)		
Aquatic			
Algae	IC50	Algae	16 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7 mg/L, 48 Hours
Distillates (Petroleum)	, Hydrotreated Ligh	nt (CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Methyl Acetate (CAS	79-20-9)		
Aquatic			
Algae	IC50	Algae	120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24

Methyl Acetate 0.18

Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

No data is available on the degradability of this product.

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Persistence and degradability

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Product name: 15 OZ TERAND MTL PLSH OIL-BASED LEMON

Product #: 1000001315 Version #: 15 Revision date: 07-27-2016 Issue date: 12-30-2014 7 /

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

DOT

**UN number** UN1950

**UN** proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 None Packaging non bulk Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

UN1950 **UN** number

**UN** proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

LTD QTY

**Packaging Exceptions** 

**IMDG** 

**UN** number UN1950 **AEROSOLS UN** proper shipping name

Transport hazard class(es)

2.1 **Class** Subsidiary risk Label(s) 2.1

Not applicable. Packing group

**Environmental hazards** 

Marine pollutant No. F-D. S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and

the IBC Code



IATA; IMDG



# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Product name: 15 OZ TERAND MTL PLSH OIL-BASED LEMON

SDS US

## **DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532

#### **US** state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Acetone (CAS 67-64-1)

#### **US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

# US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

#### **US. Rhode Island RTK**

Acetone (CAS 67-64-1) Propane (CAS 74-98-6)

### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Inventory name

Methanol (CAS 67-56-1) Listed: March 16, 2012

#### **International Inventories**

Australia

Country(s) or region

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Australian Inventory of Chemical Substances (AICS)

# 16. Other information, including date of preparation or last revision

12-30-2014 Issue date **Revision date** 07-27-2016

Version # 15

Product #: 1000001315 Version #: 15 Revision date: 07-27-2016 Issue date: 12-30-2014

On inventory (yes/no)\*

No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** 

Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Response

Product #: 1000001315 Version #: 15 Revision date: 07-27-2016 Issue date: 12-30-2014