

Revision Date: 06/10/2019

SAFETY DATA SHEET

1. Identification

Product identifier: TERAND INDUSTRIAL GLASS CLEANER

Other means of identification

SDS number: RE1000001325

Recommended restrictions

Product Use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: CPC

Address: 1000 INTEGRAM DRIVE

PACIFIC, MO 63069

Telephone: 1-800-327-1835

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition

source. Do not pierce or burn, even after use.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.



Revision Date: 06/10/2019

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Ethanol, 2-butoxy-	111-76-2	1 - <5%
2-Propanol	67-63-0	1 - <5%
Propane	74-98-6	1 - <5%
Butane	106-97-8	1 - <5%
Morpholine	110-91-8	0.1 - <1%
Ethanol, 2-methoxy-	109-86-4	0 - <0.1%
1,2-Ethanediamine	107-15-3	0 - <0.1%
Morpholine, 4-ethyl-	100-74-3	0 - <0.1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get

medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.



Revision Date: 06/10/2019

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

upwind.

Methods and material for containment and cleaning

up:

Stop the flow of material, if this is without risk. Absorb with sand or other

inert absorbent.

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer. Environmental

manager must be informed of all major spillages.

7. Handling and storage

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition

source. Do not pierce or burn, even after use.

Conditions for safe storage,

including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Aerosol Level 1

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm 120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)



Revision Date: 06/10/2019

				(1989)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm	120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
2-Propanol	REL	400 ppm	980 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	400 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	500 ppm	1,225 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	1,225 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	400 ppm	980 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	PEL	400 ppm	980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm	980 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	1,225 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL		1,225 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	200 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	400 ppm	980 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		492 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		4,920 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	_	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm	1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)



Revision Date: 06/10/2019

	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm	1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Morpholine	REL	20 ppm	70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	ST ESL		36 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	PEL	20 ppm	70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	70 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	30 ppm	105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		11 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	20 ppm	70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	105 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	30 ppm	105 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		40 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	20 ppm	70 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Ethanol, 2-methoxy-	TWA	0.1 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm	0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm	80 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	25 ppm	80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	5 ppm	16 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		16 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	PEL	25 ppm	80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		5 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11



Revision Date: 06/10/2019

				2016)
	ST ESL		160 µg/m3	US. Texas. Effects Screening Levels (Texas
	OT LOL		100 μg/1113	Commission on Environmental Quality) (11
				2016)
1,2-Ethanediamine	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
1,2 Etraricalarrino	TWA PEL	10 ppm	25 mg/m3	US. California Code of Regulations, Title 8,
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	то ррпп	20 1119/1110	Section 5155. Airborne Contaminants (09
				2006)
	PEL	10 ppm	25 mg/m3	US. OSHA Table Z-1 Limits for Air
	'	то ррпп	20 1119/1110	Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
	''''	10 ppiii	20 1119/1110	(1989)
	AN ESL		25 µg/m3	US. Texas. Effects Screening Levels (Texas
	744 202		20 μg/1110	Commission on Environmental Quality) (11
				2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas
	01 202		тоо ррь	Commission on Environmental Quality) (11
				2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas
	744 202		то ррь	Commission on Environmental Quality) (11
				2016)
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical
	INCL	то ррпп	25 mg/m5	Hazards (2005)
	ST ESL		250 µg/m3	US. Texas. Effects Screening Levels (Texas
	01 202		200 μg/1110	Commission on Environmental Quality) (11
				2016)
	TWA	10 ppm	25 mg/m3	US. Tennessee. OELs. Occupational Exposure
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	то ррпп	25 mg/m5	Limits, Table Z1A (06 2008)
Morpholine, 4-ethyl-	REL	5 ppm	23 mg/m3	US. NIOSH: Pocket Guide to Chemical
Worpholine, 4 carry	INCL	о ррш	20 1119/1110	Hazards (2005)
	TWA	5 ppm	23 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
	1 ****	о ррш	20 1119/1110	(1989)
	TWA	5 ppm	23 mg/m3	US. Tennessee. OELs. Occupational Exposure
	1 ****	о ррш	20 1119/1110	Limits, Table Z1A (06 2008)
	TWA PEL	5 ppm	23 mg/m3	US. California Code of Regulations, Title 8,
	IVVAILE	о ррпі	23 mg/m3	Section 5155. Airborne Contaminants (09
				2006)
	PEL	20 ppm	94 mg/m3	US. OSHA Table Z-1 Limits for Air
		20 ρριτί	5+ mg/ms	
	AN ESL		24 μg/m3	Contaminants (29 CFR 1910.1000) (02 2006) US. Texas. Effects Screening Levels (Texas
	/ 114 LOL		2-τ μg/1113	Commission on Environmental Quality) (11
				2016)
	TWA	5 ppm		US. ACGIH Threshold Limit Values (2008)
		o ppin	F 41	
	AN ESL		5.1 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
	OT FOL		E4 mal-	2016)
	ST ESL		51 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
	07.50		0.40 / =	2016)
	ST ESL		240 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11
				2016)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2- Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)



Revision Date: 06/10/2019

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required. Personal protection

equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: No data available.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

Vapor pressure: 4,826.3301 - 6,205.2816 hPa (20 °C)

1,068.6785 - 1,206.5725 hPa (50 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:

Solubility (other):

Partition coefficient (n-octanol/water):

No data available.

No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.



Revision Date: 06/10/2019

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 60,310.88 mg/kg

Dermal

Product: ATEmix: 21,175.09 mg/kg

Inhalation

Product: ATEmix: 690.85 mg/l

ATEmix: 172.71 mg/l

Repeated dose toxicity



Revision Date: 06/10/2019

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key

study

NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation

Experimental result, Key study

2-Propanol NOAEL (Rat, Inhalation, >= 104 Weeks): 5,000 ppm(m) Inhalation

Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Butane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Morpholine NOAEL (Rat(Female, Male), Inhalation): 36 ppm(m) Inhalation Experimental

result, Key study

LOAEL (Rat(Female), Oral, 56 d): 500 mg/kg Oral Experimental result, Key

study

Ethanol, 2-methoxy- LOAEL (Rat(Male), Oral, 90 d): 71 mg/kg Oral Experimental result, Key

study

NOAEL (Rabbit(Female, Male), Inhalation, 13 Weeks): 100 ppm(m)

Inhalation Experimental result, Key study

LOAEL (Rat(Female), Inhalation, 13 Weeks): 100 ppm(m) Inhalation

Experimental result, Supporting study

1,2-Ethanediamine NOAEL (Rat(Female, Male), Inhalation, 6 Weeks): 59 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Oral, 3 Months): 114 mg/kg Oral Experimental

result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- in vivo (Rabbit): Irritating Experimental result, Key study

2-Propanol in vivo (Rabbit): Not Classified Experimental result, Key study

Morpholine in vivo (Rabbit): Corrosive Experimental result, Key study

Ethanol, 2-methoxy- in vivo (Rabbit): Not irritant Experimental result, Key study

1,2-Ethanediamine in vivo (Rabbit): Corrosive Experimental result, Key study

Morpholine, 4-ethyl- Assessment (Various): Corrosive Expert judgment

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- Rabbit, 24 - 72 hrs: Irritating

SDS US - RE1000001325 9/16



Revision Date: 06/10/2019

10/16

2-Propanol Rabbit, 1 d: Irritating.

1,2-Ethanediamine Rabbit, 24 - 72 hrs: Corrosive

Morpholine, 4-ethyl- Corrosive

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy2-Propanol

Morpholine
Ethanol, 2-methoxy1,2-Ethanediamine

Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Ethanol, 2-methoxy- May cause adverse reproductive effects - such as infertility based on animal

data.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.



Revision Date: 06/10/2019

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key

study

2-Propanol LC 50 (Pimephales promelas, 96 h): 9,640 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Morpholine LC 50 (Oncorhynchus mykiss, 96 h): 180 mg/l Experimental result, Key

study

Ethanol, 2-methoxy- LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 14,000

- 18,000 mg/l Mortality

1,2-Ethanediamine LC 50 (Poecilia reticulata, 96 h): 640 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

2-Propanol LC 50 (Daphnia magna, 24 h): > 10,000 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Morpholine EC 50 (Daphnia magna, 48 h): 45 mg/l Experimental result, Key study

Ethanol, 2-methoxy- EC 50 (Daphnia magna, 48 h): 27,000 mg/l Experimental result, Key study

1,2-Ethanediamine EC 50 (Daphnia magna, 48 h): 16.7 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study



Revision Date: 06/10/2019

1,2-Ethanediamine NOAEL (Gasterosteus aculeatus): > 10 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study

Morpholine EC 50 (Daphnia magna): 12 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 5 mg/l Experimental result, Key study

Ethanol, 2-methoxy- NOAEL (Daphnia magna): > 500 mg/l Experimental result, Key study

1,2-Ethanediamine NOAEL (Daphnia magna): 0.16 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- 90.4 % Detected in water. Experimental result, Key study

2-Propanol 53 % (5 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Morpholine > 90 % (24 h) Sediment Experimental result, Key study

80 - 94 % (24 h) Sediment Experimental result, Key study 34.1 % Detected in water. Experimental result, Key study > 99 % (24 h) Sediment Experimental result, Key study

Ethanol, 2-methoxy- 82 % (14 d) Detected in water. Experimental result, Supporting study

74 % Detected in water. Experimental result, Key study

1,2-Ethanediamine 88 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Morpholine Cyprinus carpio, Bioconcentration Factor (BCF): < 2.8 Aquatic sediment

Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

SDS US - RE1000001325 12/16



Revision Date: 06/10/2019

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Ethanol, 2-butoxy-No data available. 2-Propanol No data available. Propane No data available. Butane No data available. Morpholine No data available. Ethanol, 2-methoxy-No data available. 1,2-Ethanediamine No data available. No data available. Morpholine, 4-ethyl-

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Wash before disposal. Dispose to controlled facilities.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2
Label(s): –
EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

SDS US - RE1000001325 13/16



Revision Date: 06/10/2019

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
2-Propanol	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
Morpholine	lbs. 100
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Flammable aerosol

SARA 302 Extremely Hazardous Substance

Reportable

Chemical IdentityquantityThreshold Planning Quantity1,2-Ethanediaminelbs. 5000lbs. 10000

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Ethanol, 2-butoxy-	
2-Propanol	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
Morpholine	lbs. 100
Ethanol, 2-methoxy-	
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
1,2-Ethanediamine	lbs
Ethanol, 2-butoxy-	10000 lbs
2-Propanol	10000 lbs
Propane	10000 lbs
Butane	10000 lbs
Morpholine	10000 lbs



Revision Date: 06/10/2019

Ethanol, 2-methoxy- 10000 lbs Morpholine, 4-ethyl- 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for manufacturing and

Chemical Identityother usersprocessingEthanol, 2-butoxy-N230 lbsN230 lbs.2-Propanollbslbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Ethanol, 2-methoxyEthanol, 2-methoxyDevelopmental toxin. 03 2008
Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Ethanol, 2-butoxy-2-Propanol Propane Butane

US. Massachusetts RTK - Substance List

Chemical Identity

1,2-Ethanediamine

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Ethanol, 2-butoxy-2-Propanol Propane Butane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Revision Date: 06/10/2019

Inventory Status:

Australia AICS: On or in compliance with the inventory

Canada DSL Inventory List: On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: On or in compliance with the inventory

China Inv. Existing Chemical Substances: On or in compliance with the inventory

Korea Existing Chemicals Inv. (KECI): On or in compliance with the inventory

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: On or in compliance with the inventory

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals:

On or in compliance with the inventory

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: On or in compliance with the inventory

Taiwan Chemical Substance Inventory:

On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 06/10/2019

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.