

SAFETY DATA SHEET

1. Identification

Product number	1000009115
Product identifier	18 OZ TERAND OVEN & GRILL CLNR LB 12PK
Revision date	03-23-2017
Company information	CPC 1005 S. Westgate Drive Addison, IL 60101 United States
Company phone	General Assistance 800-327-1835
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	02
Supersedes date	08-03-2016
Recommended use	CLEANER
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
OSHA defined hazards	Not classified.	

OSHA defined hazards

Label elements



Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.	
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.	
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, acute Category 3 hazard	
	Hazardous to the aquatic environment, Category 3 Iong-term hazard	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,2,3-Propanetriol		56-81-5	2.5 - 10
Butane		106-97-8	2.5 - 10
Potassium Hydroxide		1310-58-3	2.5 - 10
d-Limonene		5989-27-5	1 - 2.5
Polysorbate 60		9005-67-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Cocoyl Diethanolamide		68603-42-9	0.1 - 1
EDTA Tetrasodium Salt		64-02-8	0.1 - 1
Other components below reportabl	e levels		80 - 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Not available.

Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear
protective equipment and	appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch
	damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	, Value	Form
1,2,3-Propanetriol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Potassium Hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Potassium Hydroxide (CAS 1310-58-3)	TWA	2 mg/m3	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
logical limit values	No biological exposure limits noted for	the ingredient(s).	
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
ividual protection measures,	such as personal protective equipment	nt	
Eye/face protection	Wear safety glasses with side shields (recommended.	or goggles) and a face shield	. Face shield is

Skin protection Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

o. I hyoroar and onormour p	
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	233.06 °F (111.7 °C) estimated
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	50 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	1.014 estimated
10. Stability and reactivity	

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardous
reactionsHazardous polymerization does not occur.

Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Acute toxicity	May cause an allergic skill reaction	l.
Components	Species	Test Results
1,2,3-Propanetriol (CAS 56	-81-5)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	45 ml/kg, Days
Inhalation		
LC50	Rat	4655 mg.min/l, 7 Hours
Oral		
LD50	Guinea pig	>= 10000 mg/kg
	Mouse	23000 mg/kg
		20.81 ml/kg
	Rat	18300 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
d-Limonene (CAS 5989-27-	-5)	
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
EDTA Tetrasodium Salt (CA	AS 64-02-8)	
<u>Acute</u>		
Oral		
LD50	Rat	1658 mg/kg
Polysorbate 60 (CAS 9005-	-67-8)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	2325 mg/kg
Inhalation		
Aerosol		05 0070
LC50	Rat	85.0373 mg/l
Oral	Maria	
LD50	Mouse	4035.0667 mg/kg

Components	Species	1	Test Results	
	Rat	>	> 60 mg/kg	
Potassium Hydroxide (CAS 1310-	-58-3)			
<u>Acute</u>				
Oral				
LD50	Rat	3	333 mg/kg	
Propane (CAS 74-98-6)				
<u>Acute</u>				
Inhalation				
LC50	Mouse		237 mg/l, 120 Minutes	
		Ę	52 %, 120 Minutes	
	Rat	1	1355 mg/l	
		6	658 mg/l/4h	
* Estimates for product may b	be based on add	itional component data not shown.		
Skin corrosion/irritation	Causes skin i	-		
Serious eye damage/eye	Causes serior	us eye damage.		
irritation		· -		
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respirat	ory sensitizer.		
Skin sensitization	May cause ar	allergic skin reaction.		
Germ cell mutagenicity		No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.			
IARC Monographs. Overall	Evaluation of C	Carcinogenicity		
Cocoyl Diethanolamide (d-Limonene (CAS 5989- OSHA Specifically Regulat e	27-5)	3 Not classifiable as to o	ic to humans. carcinogenicity to humans.	
Not regulated. US. National Toxicology Pr	ogram (NTP) Re	eport on Carcinogens		
Not listed.				
Reproductive toxicity	This product i	s not expected to cause reproductive or de	evelopmental effects.	
Specific target organ toxicity - single exposure	Not classified			
Specific target organ toxicity - repeated exposure	Not classified			
Aspiration hazard	Not an aspira	tion hazard.		
Chronic effects	Prolonged exposure may cause chronic effects.			
12. Ecological information	n			
Ecotoxicity	Harmful to aq	uatic life with long lasting effects.		
Components		Species	Test Results	
1,2,3-Propanetriol (CAS 56-8	31-5)	•		
Aquatic	,			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	51000 - 57000 mg/l, 96 hours	
d-Limonene (CAS 5989-27-5)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours	
EDTA Tetrasodium Salt (CAS	S 64-02-8)		-	
Aquatic				
Algae	IC50	Algae	1.01 mg/L, 72 Hours	

Components		Species	Test Results
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours
Potassium Hydroxide (CAS 1	310-58-3)		
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affi	inis) 80 mg/l, 96 hours
* Estimates for product may I	be based on	additional component data not shown.	
Persistence and degradability	No data i	s available on the degradability of this prod	uct.
Bioaccumulative potential			
Partition coefficient n-octa 1,2,3-Propanetriol Butane d-Limonene Propane	nol / water (log Kow) -1.76 2.89 4.232 2.36	
Mobility in soil	No data a	available.	
Other adverse effects		adverse environmental effects (e.g. ozone e endocrine disruption, global warming poter	
13. Disposal consideratio	ns		
Disposal instructions	under pre sewers/w		. Do not allow this material to drain into
Local disposal regulations	Dispose i	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.		
14. Transport information	1		
рот			
UN number	UN1950		
UN proper shipping name		flammable, (each not exceeding 1 L capac	ity)
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Label(s)	2.1		

Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.

Environmental hazards ERG Code Special precautions for user Other information	No. 10L Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only Packaging Exceptions	Allowed with restrictions. LTD QTY
IMDG UN number UN proper shipping name Transport hazard class(es)	UN1950 AEROSOLS
Class Subsidiary risk Label(s)	2.1 - 2.1
Packing group Environmental hazards	Not applicable.
Marine pollutant EmS	No. F-D, S-U
Special precautions for user Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.

DOT





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Potassium Hydroxide (CAS 1310-58-3) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8) Cocoyl Diethanolamide (CAS 68603-42-9)

US. Massachusetts RTK - Substance List

1,2,3-Propanetriol (CAS 56-81-5) Butane (CAS 106-97-8) Potassium Hydroxide (CAS 1310-58-3) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

1,2,3-Propanetriol (CAS 56-81-5) Butane (CAS 106-97-8) Potassium Hydroxide (CAS 1310-58-3) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,3-Propanetriol (CAS 56-81-5) Butane (CAS 106-97-8) Potassium Hydroxide (CAS 1310-58-3) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Potassium Hydroxide (CAS 1310-58-3) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988
US - California Proposition 65 - CRT: Listed	date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-03-2016
Revision date	03-23-2017
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.