SAFETY DATA SHEET

1. Identification

Product number 1000001352

Product identifier 7 OZ TERAND CITRUS MTRD AIR FRSHNR LB

Revision date 03-09-2016

Company information CPC

1005 S. Westgate Drive

Addison, IL 60101 United States

Company phone General Assistance 800-327-1835

Emergency telephone US
Emergency telephone outside

1-866-836-8855

1-952-852-4646

US

Version # 06

Supersedes date 10-25-2015

Recommended use Air Freshener

Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	hemical name Common name and synonyms		%	
Acetone		67-64-1	60 - 80	
Butane		106-97-8	10 - 20	

Product name: 7 OZ TERAND CITRUS MTRD AIR FRSHNR LB

Product #: 1000001352 Version #: 06 Revision date: 03-09-2016 Issue date: 10-22-2014 1 / 10

SDS US

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	10 - 20
Diethylene Glycol Monoethyl Eth	ner	111-90-0	2.5 - 10
Other components below reports	able levels		2.5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Most important

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

symptoms/effects, acute and

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

delayed

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

Specific methods

equipment/instructions

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants	(29 CFR	1910 1000)
03. OSHA Table 2-1 Lilling for All Contaminants	(23 01 11	1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
US. Workplace Environmental E	xposure Level (WEEL) Guides		
Components	Туре	Value	
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	TWA	140 mg/m3	
·		25 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove Hand protection

supplier.

Wear suitable protective clothing. Other

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas. **Form** Aerosol. Not available. Color Odor Not available. Not available. **Odor threshold** Not available. pН Not available. Melting point/freezing point

Initial boiling point and boiling

range

132.89 °F (56.05 °C) estimated

-156.0 °F (-104.4 °C) Propellant estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits 2.4 % estimated

Flammability limit - lower

(%)

Flammability limit - upper

11.9 % estimated

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

55 psig @20C estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. Viscosity

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing. Specific gravity 0.173 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Narcotic effects.

omponents	Species	Test Results
cetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		- 400 # 0444
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
utane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
iethylene Glycol Monoethyl	Ether (CAS 111-90-0)	
<u>Acute</u>		
Dermal	Cuinag nig	5000 mg/kg. Dayo
LD50	Guinea pig	5900 mg/kg, Days
	Rabbit	9143 mg/kg, 24 Hours
		8500 mg/kg, 2 Hours
Oral	Outro a min	4070
LD50	Guinea pig	4970 mg/kg
	Mouse	6031 mg/kg
	Rabbit	5600 mg/kg
	Rat	10502 mg/kg
		5.4 ml/kg

Product name: 7 OZ TERAND CITRUS MTRD AIR FRSHNR LB

SDS US

Components	Species	Test Results
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

May cause drowsiness and dizziness.

single exposure

Chronic effects

Specific target organ toxicity -

Not classified.

repeated exposure
Aspiration hazard

Not likely, due to the form of the product. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

D AIR FRSHN EC50 LC50	NR LB Daphnia Fish Species	15254.5645 mg/l, 48 hours estimated 10391.9893 mg/l, 96 hours estimated Test Results
	Fish	10391.9893 mg/l, 96 hours estimated
	Fish	10391.9893 mg/l, 96 hours estimated
LC50		
	Species	Test Results
EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Ether (CAS 11	11-90-0)	
LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours
-	LC50 Ether (CAS 11	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) Ether (CAS 111-90-0)

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Product name: 7 OZ TERAND CITRUS MTRD AIR FRSHNR LB

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

-0.24Acetone 2.89 Butane Diethylene Glycol Monoethyl Ether -0.54Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

2.1 Class **Subsidiary risk** 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

N82 Special provisions 306 Packaging exceptions Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number

Aerosols, flammable **UN proper shipping name**

Transport hazard class(es)

Class 2.1 **Subsidiary risk** Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 **UN proper shipping name AEROSOLS**

Transport hazard class(es)

Class 2.1 **Subsidiary risk**

Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutantNo.EmSF-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY
Transport in bulk according to Not applicable.
Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Product name: 7 OZ TERAND CITRUS MTRD AIR FRSHNR LB

sds us 8 / 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1) Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region On inventory (yes/no)* Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

10-22-2014 Issue date **Revision date** 03-09-2016

Version # 06

Disclaimer We cannot anticipate all conditions under which this information and its product, or the products of

> other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Product and Company Identification: Alternate Trade Names **Revision information**

Regulatory Information: Canada

Product #: 1000001352 Version #: 06 Revision date: 03-09-2016 Issue date: 10-22-2014 10 / 10