

SAFETY DATA SHEET

1. Identification	
Product number	1000009139
Product identifier	TERAND CUTTING AND TAPPING FLUID
Company information	CPC 1005 S. Westgate Drive Addison, IL 60101 United States
Company phone	General Assistance 800-327-1835
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	Lubricant
Recommended restrictions	None known.
2. Hazard(s) identification	

· · ·		
Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger		
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.		
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.		

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Acetone		67-64-1	40 - 60	
Butane		106-97-8	10 - 20	
Propane		74-98-6	2.5 - 10	_
Other components below reportable levels			20 - 40	_
Product name: TERAND CUTTI	NG AND TAPPING FLUID			SDS US
Product #: 1000009139 Version #: 01 Issue date: 10-06-2016				1/9

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Product name: TERAND CUTTING AN	D TAPPING FLUID	SDS US
Product #: 1000009139 Version #: 01	Issue date: 10-06-2016	2 / 9

Conditions for safe storage,
including any incompatibilitiesLevel 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре		, v	alue	
Acetone (CAS 67-64-1)	PEL		24	400 mg/m3	
			10	000 ppm	
Propane (CAS 74-98-6)	PEL		18	800 mg/m3	
			10	000 ppm	
US. ACGIH Threshold Li	mit Values				
Components	Туре		V	alue	
Acetone (CAS 67-64-1)	STEL	-	50	00 ppm	
	TWA		2	50 ppm	
Butane (CAS 106-97-8)	STEL		10	000 ppm	
US. NIOSH: Pocket Guid	le to Chemical Hazards				
Components	Туре		v	alue	
Acetone (CAS 67-64-1)	TWA		59	90 mg/m3	
			2	50 ppm	
Butane (CAS 106-97-8)	TWA		19	900 mg/m3	
			80	00 ppm	
Propane (CAS 74-98-6)	TWA		18	800 mg/m3	
iological limit values ACGIH Biological Expos Components	sure Indices Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, p	0		Child		
ppropriate engineering ontrols	Good general ventila should be matched or other engineering	ation (typically 10 to conditions. If a controls to main	oplicable, use pro tain airborne leve	hour) should be used. Vent ocess enclosures, local exh els below recommended ex irborne levels to an accepta	aust ventilation, posure limits. If
dividual protection measu Eye/face protection	res, such as personal pr Wear safety glasses				
Skin protection Hand protection	Wear appropriate ch supplier.	nemical resistant	gloves. Suitable	gloves can be recommende	ed by the glove
Other	Wear suitable prote	ctive clothing.			
Respiratory protection	·	are exceeded us	e NIOSH mecha	nical filter / organic vapor ca	artridge or an

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SDS US 3 / 9

9. Physical and chemical properties

Appearance

Physical stateGas.FormAerosol.

Product name: TERAND CUTTING AND TAPPING FLUID Product #: 1000009139 Version #: 01 Issue date: 10-06-2016

Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	90.85 °F (32.7 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.6 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	238.12 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Flame extension	48 in
Oxidizing properties	Not oxidizing.
Specific gravity	0.175 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

SDS US 4 / 9

Product name: TERAND	CUTTING AND) TAPPING FLUID
Product #: 1000009139	Version #: 01	Issue date: 10-06-2016

Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		-
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
* Estimatos for product may l	he haved on additional component data	not chown
Skin corrosion/irritation	be based on additional component data Prolonged skin contact may cause to	
Skin corrosion/irritation Serious eye damage/eye	Causes serious eye irritation.	
rritation	Causes senous eye initation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to caus	e skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
	indiagenie of genoloxie.	

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

city - May cause drowsiness and dizziness.

Product name: TERAND CUTTING AND TAPPING FLUIDSDS USProduct #: 1000009139Version #: 01Issue date: 10-06-20165 / 9

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
TERAND CUTTING A	ND TAPPING FLU	ID	
Aquatic			
Crustacea	EC50	Daphnia	22251.1855 mg/l, 48 hours estimated
Fish	LC50	Fish	1096.5597 mg/l, 96 hours estimated
Components		Species	Test Results
Acetone (CAS 67-64-7	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)
Acetone	-0.24
Butane	2.89
Propane	2.36
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950	
UN proper shipping name	Aerosols, flammable	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Label(s)	2.1	
Packing group	Not applicable.	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
Special provisions	N82	
Packaging exceptions	306	
Packaging non bulk	None	
Product name: TERAND CUTTING A	ND TAPPING FLUID	SDS US
Product #: 1000009139 Version #: 0'	I Issue date: 10-06-2016	6 / 9

Packaging bulk IATA	None
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Product name: TERAND CUTTING AND	TAPPING FLUID	SDS US
Product #: 1000009139 Version #: 01	Issue date: 10-06-2016	7 / 9

TSCA Section 12(b) Export	Notification (40 CFR 707, Subj	ot. D)
Not regulated.		
CERCLA Hazardous Substa	nce List (40 CFR 302.4)	
Acetone (CAS 67-64-1)		Listed.
SARA 304 Emergency relea	se notification	
Not regulated.		
	ed Substances (29 CFR 1910.1	001-1050)
Not regulated.		
Superfund Amendments and Re	•	RA)
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazar	dous substance	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants	s (HAPs) List
Not regulated.		
Clean Air Act (CAA) Section	n 112(r) Accidental Release Pre	evention (40 CFR 68.130)
Butane (CAS 106-97-8) Propane (CAS 74-98-6)		
Safe Drinking Water Act (SDWA)	Not regulated.	
Drug Enforcement Adm Chemical Code Numbe		ntial Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and
Acetone (CAS 67-64	-1)	6532
Drug Enforcement Adm	ninistration (DEA). List 1 & 2 E	xempt Chemical Mixtures (21 CFR 1310.12(c))
Acetone (CAS 67-64		35 %WV
•	Mixtures Code Number	
Acetone (CAS 67-64	-1)	6532
US state regulations		
US. California Controlled S	ubstances. CA Department of	Justice (California Health and Safety Code Section 11100)
Not listed.		
US. California. Candidate C (a))	hemicals List. Safer Consume	r Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.
Acetone (CAS 67-64-1) Butane (CAS 106-97-8)		
US. Massachusetts RTK - S	ubstance List	
Acetone (CAS 67-64-1)		
Butane (CAS 106-97-8)		
Propane (CAS 74-98-6)	I Community Right-to-Know A	ct
US. New Jersey worker and		

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Product name: TERAND CUTTING AND TAPPING FLUID Product #: 1000009139 Version #: 01 Issue date: 10-06-2016 sds us 8 / 9

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988	
Ethylene Oxide (CAS 75-21-8)	Listed: July 1, 1987	
Propylene Oxide (CAS 75-56-9)	Listed: October 1, 1988	
US - California Proposition 65 - CRT: Listed	date/Developmental toxin	
Ethylene Oxide (CAS 75-21-8)	Listed: August 7, 2009	
US - California Proposition 65 - CRT: Listed	date/Female reproductive toxin	
Ethylene Oxide (CAS 75-21-8)	Listed: February 27, 1987	
US - California Proposition 65 - CRT: Listed date/Male reproductive toxin		
Ethylene Oxide (CAS 75-21-8)	Listed: August 7, 2009	

Ethylene Oxide (CAS 75-21-8)	Listed: Augus

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Version #	10-06-2016 01
Disclaimer	We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Product and Company Identification: Alternate Trade Names

Product name: TERAND CUTTING AND TAPPING FLUID	SDS US
Product #: 1000009139 Version #: 01 Issue date: 10-06-2016	9 / 9