



# SAFETY DATA SHEET

## 1. Identification

Product number 1000011618  
Product identifier 16 OZ SEYMR GLS WHITE IND COAT LB 6PK  
Company information CPC  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
Company phone Emergency General Assistance 800-327-1835  
telephone US Emergency 1-866-836-8855  
telephone outside US 1-952-852-4646  
Version # Recommended 01  
use Recommended COATING  
restrictions None known.

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1  
Health hazards Serious eye damage/eye irritation Category 2A  
OSHA defined hazards Not classified.

### Label elements



Signal word Danger  
Hazard statement Extremely flammable aerosol. Causes serious eye irritation.  
Precautionary statement  
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.  
Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Disposal Dispose of waste and residues in accordance with local authority requirements.  
Hazard(s) not otherwise classified (HNOC) None known.  
Supplemental information None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	10 - 20
Propane		74-98-6	10 - 20
Titanium dioxide		13463-67-7	10 - 20
Barium Sulfate, Natural		7727-43-7	2.5 - 10
Butane		106-97-8	2.5 - 10
Ethylene Glycol Propyl Ether		2807-30-9	2.5 - 10
Isobutyl Acetate		110-19-0	2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
Methyl Isobutyl Ketone		108-10-1	2.5 - 10
Methyl Propyl Ketone		107-87-9	2.5 - 10
Xylene		1330-20-7	1 - 2.5
Other components below reportable levels			20 - 40

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
Barium Sulfate, Natural (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
Isobutyl Acetate (CAS 110-19-0)	PEL	15 mg/m3 700 mg/m3	Total dust.
Methyl Isobutyl Ketone (CAS 108-10-1)	PEL	150 ppm 410 mg/m3	
Methyl Propyl Ketone (CAS 107-87-9)	PEL	100 ppm 700 mg/m3	
Propane (CAS 74-98-6)	PEL	200 ppm 1800 mg/m3	
Titanium dioxide (CAS 13463-67-7)	PEL	1000 ppm	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Barium Sulfate, Natural (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Butane (CAS 106-97-8)	STEL	1000 ppm	
Isobutyl Acetate (CAS 110-19-0)	TWA	150 ppm	
Methyl Isobutyl Ketone (CAS 108-10-1)	STEL	75 ppm	
	TWA	20 ppm	
Methyl Propyl Ketone (CAS 107-87-9)	STEL	150 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	590 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards  
Components

Type	Value	Form
Barium Sulfate, Natural (CAS 7727-43-7)	250 ppm 5 mg/m3	Respirable.
Butane (CAS 106-97-8)	10 mg/m3 1900 mg/m3	Total
Isobutyl Acetate (CAS 110-19-0)	800 ppm 700 mg/m3	
Methyl Isobutyl Ketone (CAS 108-10-1)	150 ppm 300 mg/m3	
Methyl Propyl Ketone (CAS 107-87-9)	75 ppm 205 mg/m3 50 ppm 530 mg/m3	
Propane (CAS 74-98-6)	150 ppm 1800 mg/m3 1000 ppm	

Biological limit values

ACGIH Biological Exposure Components	Indices Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Methyl Isobutyl Ketone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin protection**

  - Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
  - Other** Wear suitable protective clothing.

- Respiratory protection** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
- Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	-47.2 °F (-44 °C) supplier estimated
Flash point	-2.2 °F (-19.0 °C) supplier
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.7 supplier
Flammability limit - upper (%)	10.9 supplier
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	1.163 estimated

## 10. Stability and reactivity

Reactivity Chemical stability	The product is stable and non-reactive under normal conditions of use, storage and transport.
Possibility of hazardous reactions	Material is stable under normal conditions. Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

Information on likely routes of exposure	
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Information on toxicological effects	
Acute toxicity	

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Barium Sulfate, Natural (CAS 7727-43-7)		
<u>Acute</u>		
Oral		
LD100	Rat	564 g/kg
LD50	Rat	307 g/kg
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Ethylene Glycol Propyl Ether (CAS 2807-30-9)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	5.6 g/kg, 4 Days
	Rabbit	> 1 g/kg, 24 Hours 1337 ml/kg, 14 Days
Inhalation		
LC50	Rat	> 2132 ppm, 6 Hours > 1800 ppm
Oral		
LD50	Guinea pig	2.2 g/kg
	Mouse	1774 mg/kg
	Rat	0.5 - 1 g/kg
Isobutyl Acetate (CAS 110-19-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 17400 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 30 mg/l, 6 Hours > 23.4 mg/l, 4 Hours
Oral		
LD50	Rat	13413 mg/kg

Components	Species	Test Results
Methyl Isobutyl Ketone (CAS 108-10-1)		
<u>Acute</u>		
Inhalation		
LC50	Rat	2000 - 4000 ppm, 4 Hours
Oral		
LD50	Rat	2.08 g/kg
Methyl Propyl Ketone (CAS 107-87-9)		
<u>Acute</u>		
Inhalation		
Vapor		
LC50	Rat	> 25.5 mg/l, 4 Hours
Oral		
LD50	Mouse	1600 mg/kg
	Rat	1600 - 3200 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Titanium dioxide (CAS 13463-67-7)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 2.28 mg/l, 4 Hours
Oral		
LD50	Mouse	> 5000 mg/kg
	Rat	> 2000 mg/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 ml/kg, 4 Hours 12126 mg/kg, 24 Hours
Inhalation		
LC50	Rat	5922 ppm, 4 Hours
Oral		
LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg 10 ml/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Isobutyl Ketone (CAS 108-10-1) 2B Possibly carcinogenic to humans.  
 Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.  
 Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
Barium Sulfate, Natural (CAS 7727-43-7)		
Aquatic		
Crustacea	EC50	Tubificid worm (Tubifex tubifex) 28.61 - 38.03 mg/l, 48 hours
Methyl Isobutyl Ketone (CAS 108-10-1)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours
Methyl Propyl Ketone (CAS 107-87-9)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 1190 - 1290 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
Acetone	-0.24
Butane	2.89
Isobutyl Acetate	1.78
Methyl Isobutyl Ketone	1.31
Methyl Propyl Ketone	0.91
Propane	2.36
Xylene	3.12 - 3.2

Mobility in soil No data available.



Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

#### DOT

UN number UN1950  
UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)  
Transport hazard class(es)  
Class 2.1  
Subsidiary risk -  
Label(s) 2.1  
Packing group Not applicable.  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.  
Special provisions N82  
Packaging exceptions 306  
Packaging non bulk None  
Packaging bulk None

#### IATA

UN number UN1950  
UN proper shipping name Aerosols, flammable  
Transport hazard class(es)  
Class 2.1  
Subsidiary risk -  
Label(s) Packing 2.1  
group Environmental Not applicable.  
hazards ERG Code No.  
10L  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.  
Other information  
Passenger and cargo aircraft Allowed with restrictions.  
Cargo aircraft only Allowed with restrictions.  
Packaging Exceptions LTD QTY

#### IMDG

UN number UN1950  
UN proper shipping name AEROSOLS  
Transport hazard class(es)  
Class 2.1  
Subsidiary risk -  
Label(s) Packing 2.1  
group Environmental Not applicable.  
hazards  
Marine pollutant No.  
EmS F-D, S-U  
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.  
Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.  
 DOT



IATA; IMDG



**15. Regulatory information**

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)  
 Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)  
 Acetone (CAS 67-64-1) Listed.  
 Isobutyl Acetate (CAS 110-19-0) Listed.  
 Methyl Isobutyl Ketone (CAS 108-10-1) Listed.  
 Xylene (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification  
 Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)  
 Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes  
 Delayed Hazard - No  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance  
 Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methyl Isobutyl Ketone	108-10-1	2.5 - 10
Xylene	1330-20-7	1 - 2.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List  
 Methyl Isobutyl Ketone (CAS 108-10-1)  
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Methyl Isobutyl Ketone (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Methyl Isobutyl Ketone (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Methyl Isobutyl Ketone (CAS 108-10-1) 6715

#### US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Methyl Isobutyl Ketone (CAS 108-10-1)

Titanium dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Barium Sulfate, Natural (CAS 7727-43-7)

Butane (CAS 106-97-8)

Isobutyl Acetate (CAS 110-19-0)

Methyl Isobutyl Ketone (CAS 108-10-1)

Methyl Propyl Ketone (CAS 107-87-9)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Barium Sulfate, Natural (CAS 7727-43-7)

Butane (CAS 106-97-8)

Isobutyl Acetate (CAS 110-19-0)

Methyl Isobutyl Ketone (CAS 108-10-1)

Methyl Propyl Ketone (CAS 107-87-9)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Barium Sulfate, Natural (CAS 7727-43-7)

Butane (CAS 106-97-8)

Isobutyl Acetate (CAS 110-19-0)

Methyl Isobutyl Ketone (CAS 108-10-1)

Methyl Propyl Ketone (CAS 107-87-9)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Isobutyl Acetate (CAS 110-19-0)

Methyl Isobutyl Ketone (CAS 108-10-1)

Propane (CAS 74-98-6)

Xylene (CAS 1330-20-7)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methyl Isobutyl Ketone (CAS 108-10-1) Listed: November 4, 2011

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methyl Isobutyl Ketone (CAS 108-10-1) Listed: March 28, 2014

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 07-12-2016

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.