



SAFETY DATA SHEET

1. Identification

Product number 1000011632
Product identifier 12Z SEYMR 6 PK RED IRON OXIDE LB 16-807
Revision date 08-25-2016
Company information CPC
1000 INTEGRAM DRIVE
PACIFIC, MO 63069 United States
Company phone General Assistance 800-327-1835
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 02-23-2015
Recommended use Coating
Recommended restrictions None known.

2. Hazard(s) identification

| | | |
|-----------------------------|---|-----------------------------|
| Physical hazards | Flammable aerosols | Category 1 |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2A |
| | Reproductive toxicity (the unborn child) | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Specific target organ toxicity, repeated exposure | Category 2 |
| | Aspiration hazard | Category 1 |
| OSHA defined hazards | Not classified. | |

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

| | |
|--|--|
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard Category 2 Hazardous to the aquatic environment, long-term hazard Category 2 |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|----------|
| Acetone | | 67-64-1 | 20 - 40 |
| Propane | | 74-98-6 | 10 - 20 |
| Butane | | 106-97-8 | 2.5 - 10 |
| Ethyl Alcohol | | 64-17-5 | 2.5 - 10 |
| Magnesium Silicate | | 14807-96-6 | 2.5 - 10 |
| n-Butyl Acetate | | 123-86-4 | 2.5 - 10 |
| Red Iron Oxide Pigment | | 1309-37-1 | 2.5 - 10 |
| Solvent naphtha (petroleum), light aliph. | | 64742-89-8 | 2.5 - 10 |
| Toluene | | 108-88-3 | 2.5 - 10 |
| Xylene | | 1330-20-7 | 2.5 - 10 |
| Isobutyl Acetate | | 110-19-0 | 1 - 2.5 |
| Propylene Glycol Monomethyl Ether Acetate | | 108-65-6 | 1 - 2.5 |
| Other components below reportable levels | | | 10 - 20 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

5. Fire-fighting measures

| | |
|---|---|
| Suitable extinguishing media | Alcohol resistant foam. Powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |

| | |
|--|--|
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---------------------------------|------|------------------------|------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 1000 ppm | |
| Ethyl Alcohol (CAS 64-17-5) | PEL | 1900 mg/m3 1000 ppm | |
| Isobutyl Acetate (CAS 110-19-0) | PEL | 700 mg/m3 | |
| n-Butyl Acetate (CAS 123-86-4) | PEL | 150 ppm 710 mg/m3 | |
| Propane (CAS 74-98-6) | PEL | 150 ppm 1800 mg/m3 | |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|----------------------|-------|
| Red Iron Oxide Pigment (CAS 1309-37-1) | PEL | 1000 ppm 10 mg/m3 | Fume. |
| Xylene (CAS 1330-20-7) | PEL | 435 mg/m3 100 ppm | |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value | |
|------------------------|---------|---------|--|
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm | |
| | TWA | 200 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|-----------|-------------|
| Magnesium Silicate (CAS 14807-96-6) | TWA | 0.3 mg/m3 | Total dust. |
| | | 0.1 mg/m3 | Respirable. |
| | | 20 mppcf | |
| | | 2.4 mppcf | Respirable. |

ACGIH

| Components | Type | Value | |
|--|------|---------|--|
| Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | TWA | 400 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|----------|----------------------|
| Acetone (CAS 67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| Butane (CAS 106-97-8) | STEL | 1000 ppm | |
| Ethyl Alcohol (CAS 64-17-5) | STEL | 1000 ppm | |
| Isobutyl Acetate (CAS 110-19-0) | TWA | 150 ppm | |
| Magnesium Silicate (CAS 14807-96-6) | TWA | 2 mg/m3 | Respirable fraction. |
| n-Butyl Acetate (CAS 123-86-4) | STEL | 200 ppm | |
| | TWA | 150 ppm | |
| Red Iron Oxide Pigment (CAS 1309-37-1) | TWA | 5 mg/m3 | Respirable fraction. |
| Toluene (CAS 108-88-3) | TWA | 20 ppm | |
| Xylene (CAS 1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|------|------------------------|-------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 250 ppm | |
| Butane (CAS 106-97-8) | TWA | 1900 mg/m3 800 ppm | |
| Ethyl Alcohol (CAS 64-17-5) | TWA | 1900 mg/m3 1000 ppm | |
| Isobutyl Acetate (CAS 110-19-0) | TWA | 700 mg/m3 150 ppm | |
| Magnesium Silicate (CAS 14807-96-6) | TWA | 2 mg/m3 | Respirable. |
| n-Butyl Acetate (CAS 123-86-4) | STEL | 950 mg/m3 | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|------|------------|----------------|
| Propane (CAS 74-98-6) | TWA | 200 ppm | |
| | | 710 mg/m3 | |
| | | 150 ppm | |
| Red Iron Oxide Pigment (CAS 1309-37-1) | TWA | 1800 mg/m3 | Dust and fume. |
| | | 1000 ppm | |
| | | 5 mg/m3 | |
| Toluene (CAS 108-88-3) | STEL | 560 mg/m3 | |
| | | 150 ppm | |
| | | 375 mg/m3 | |
| | TWA | 100 ppm | |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value |
|--|------|--------|
| Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | TWA | 50 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------|----------|---------------------------|---------------------|---------------|
| Acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | | Toluene | Urine | * |
| | | Toluene | Blood | * |
| | | Methylhippuric acids | Creatinine in urine | * |
| Xylene (CAS 1330-20-7) | 1.5 g/g | | | |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) Can be absorbed through the skin.
Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

| | |
|---|-----------------------------|
| Form | Aerosol. |
| Color | Not available. |
| Odor | Not available. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | -47.2 °F (-44 °C) estimated |
| Flash point | 8.6 °F (-13.0 °C) estimated |
| Evaporation rate | > 1 BuAc |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 2.3 % estimated |
| Flammability limit - upper (%) | 11.6 % estimated |
| Explosive limit - lower (%) | 1.7 % estimated |
| Explosive limit - upper (%) | 10.9 % estimated |
| Vapor pressure | 40 psig @70F estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |
| Heat of combustion (NFPA 30B) | 31 kJ/g estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 78.2 % estimated |
| Specific gravity | 0.81 estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

| Components | Species | Test Results |
|---------------------------------|----------------|--|
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| Dermal | | |
| LD50 | Guinea pig | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours |
| | Rabbit | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l |
| Oral | | |
| LD50 | Rat | 5800 mg/kg 2.2 ml/kg |
| Butane (CAS 106-97-8) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| Ethyl Alcohol (CAS 64-17-5) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Cat | 85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours |
| | Mouse | > 60000 ppm 79.43 mg/l, 134 Minutes |
| | Rat | > 115.9 mg/l, 4 Hours 51.3 mg/l, 6 Hours |
| Oral | | |
| LD50 | Monkey | 6000 mg/kg |
| | Mouse | 10500 ml/kg |
| | Pig | > 5000 mg/kg |
| | Rat | 10470 mg/kg 7800 ml/kg |
| Isobutyl Acetate (CAS 110-19-0) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 17400 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | > 30 mg/l, 6 Hours > 23.4 mg/l, 4 Hours |

| Components | Species | Test Results |
|--|---------|--|
| Oral | | |
| LD50 | Rat | 13413 mg/kg |
| n-Butyl Acetate (CAS 123-86-4) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 16 ml/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 1087 ppm, 4 Hours 0.74 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | 14130 mg/kg 12.2 ml/kg |
| Propane (CAS 74-98-6) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes 52 %, 120 Minutes |
| | Rat | 1355 mg/l 658 mg/l/4h |
| Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rat | > 2000 mg/kg, 24 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg > 14.1 ml |
| Red Iron Oxide Pigment (CAS 1309-37-1) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 1900 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | > 5000 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | 4820 mg/kg |
| Toluene (CAS 108-88-3) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 5000 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Mouse | 6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours |
| | Rat | 5879 - 6281 ppm, 6 Hours |

| Components | Species | Test Results |
|------------------------|---------|--|
| | | 25.7 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Xylene (CAS 1330-20-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 5000 ml/kg, 4 Hours 12126 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 5922 ppm, 4 Hours |
| Oral | | |
| LD50 | Mouse | 5251 mg/kg |
| | Rat | 3523 mg/kg |
| | | 10 ml/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|---|---|
| Skin corrosion/irritation | Causes skin irritation. |
| Serious eye damage/eye irritation | Causes serious eye irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | Risk of cancer cannot be excluded with prolonged exposure. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| Magnesium Silicate (CAS 14807-96-6) | 2B Possibly carcinogenic to humans. |
| Red Iron Oxide Pigment (CAS 1309-37-1) | 3 Not classifiable as to carcinogenicity to humans. |
| Toluene (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. |
| Xylene (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | |
| | Not regulated. |
| US. National Toxicology Program (NTP) Report on Carcinogens | |
| | Not listed. |
| Reproductive toxicity | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child. |
| Specific target organ toxicity - single exposure | May cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | May be fatal if swallowed and enters airways. |
| Chronic effects | May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

| Components | Species | Test Results |
|-----------------------|---------|--------------------------------|
| Acetone (CAS 67-64-1) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| | | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout |
| | | (Oncorhynchus mykiss) |
| | | 4740 - 6330 mg/l, 96 hours |

| Components | Species | Test Results |
|--|---------|---|
| Ethyl Alcohol (CAS 64-17-5) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 7700 - 11200 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours |
| n-Butyl Acetate (CAS 123-86-4) | | |
| Aquatic | | |
| Algae | IC50 | Algae 674.7 mg/L, 72 Hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours |
| Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) | | |
| Aquatic | | |
| Crustacea | EC50 | Daphnia 500.0001 mg/L, 48 Hours |
| Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | | |
| Aquatic | | |
| Algae | IC50 | Algae 4700 mg/L, 72 Hours |
| Toluene (CAS 108-88-3) | | |
| Aquatic | | |
| Algae | IC50 | Algae 433.0001 mg/L, 72 Hours |
| Crustacea | EC50 | Daphnia 7.645 mg/L, 48 Hours |
| | | Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours |
| Xylene (CAS 1330-20-7) | | |
| Aquatic | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|------------------|------------|
| Acetone | -0.24 |
| Butane | 2.89 |
| Ethyl Alcohol | -0.31 |
| Isobutyl Acetate | 1.78 |
| n-Butyl Acetate | 1.78 |
| Propane | 2.36 |
| Toluene | 2.73 |
| Xylene | 3.12 - 3.2 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information**DOT**

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, (each not exceeding 1 L capacity) |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Environmental hazards | Yes |
| ERG Code | 10L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |
| Packaging Exceptions | LTD QTY |

IMDG

| | |
|---|---|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| EmS | F-D, S-U |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Packaging Exceptions | LTD QTY |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |


DOT



IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|---------------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Isobutyl Acetate (CAS 110-19-0) | Listed. |
| n-Butyl Acetate (CAS 123-86-4) | Listed. |
| Toluene (CAS 108-88-3) | Listed. |
| Xylene (CAS 1330-20-7) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| Toluene | 108-88-3 | 2.5 - 10 |
| Xylene | 1330-20-7 | 2.5 - 10 |

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV
Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Magnesium Silicate (CAS 14807-96-6)
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Ethyl Alcohol (CAS 64-17-5)
Isobutyl Acetate (CAS 110-19-0)
Magnesium Silicate (CAS 14807-96-6)
n-Butyl Acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Red Iron Oxide Pigment (CAS 1309-37-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Ethyl Alcohol (CAS 64-17-5)
Isobutyl Acetate (CAS 110-19-0)
Magnesium Silicate (CAS 14807-96-6)
n-Butyl Acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Red Iron Oxide Pigment (CAS 1309-37-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Ethyl Alcohol (CAS 64-17-5)
Isobutyl Acetate (CAS 110-19-0)

Magnesium Silicate (CAS 14807-96-6)
n-Butyl Acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Red Iron Oxide Pigment (CAS 1309-37-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Butane (CAS 106-97-8)
Isobutyl Acetate (CAS 110-19-0)
n-Butyl Acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 02-23-2015

Revision date 08-25-2016

Version # 02

Disclaimer We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.