SAFETY DATA SHEET

1. Identification

Product number 1000011638

Product identifier 17z SEYMR ORNG FLRSCNT MRKNG PNT 20-657

Company information

1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States

General Assistance 800-327-1835 Company phone

1-866-836-8855 **Emergency telephone US Emergency telephone outside** 1-952-852-4646

US

01

Version # Recommended use Coating **Recommended restrictions** None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Aspiration hazard Category 1 **Health hazards**

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. **Hazard statement**

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Response

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage **Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	10 - 20
Propane		74-98-6	10 - 20
Solvent naphtha (petroleum), light aliph.		64742-89-8	10 - 20
Butane		106-97-8	2.5 - 10
Isobutyl Acetate		110-19-0	2.5 - 10
Other components below reportable le	evels		40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product name: 17z SEYMR ORNG FLRSCNT MRKNG PNT 20-657 Product #: 1000011638 Version #: 01 Issue date: 04-20-2017

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation.

medical attention and special Symptoms may be delayed. treatment needed

Aspiration may cause pulmonary edema and pneumonitis.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information** protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Oc

PEL PEL PEL Type TWA ues Type STEL TWA emical Hazards Type TWA	5 mg/m3 15 mg/m3 700 mg/m3 150 ppm 1800 mg/m3 1000 ppm Value 400 ppm 1000 ppm 150 ppm 150 ppm	Respirable fraction. Total dust. Form	
Type TWA ues Type STEL TWA temical Hazards Type	700 mg/m3 150 ppm 1800 mg/m3 1000 ppm Value 400 ppm Value 1000 ppm 150 ppm		
Type TWA ues Type STEL TWA emical Hazards Type	1800 mg/m3 1000 ppm Value 400 ppm Value 1000 ppm 150 ppm Value	Form	
TWA TWA Type STEL TWA TWA Type Type	Value 1000 ppm 150 ppm	Form	
TWA TWA Type STEL TWA TWA Type Type	Value 1000 ppm 150 ppm	Form	
ues Type STEL TWA remical Hazards Type	Value 1000 ppm 150 ppm	Form	
Type STEL TWA semical Hazards Type	1000 ppm 150 ppm Value	Form	
STEL TWA emical Hazards Type	1000 ppm 150 ppm Value	Form	
TWA emical Hazards Type	150 ppm Value	Form	
emical Hazards Type	Value	Form	
Туре		Form	
TWA	1900 ma/m3		
	800 ppm		
TWA	5 mg/m3	Respirable.	
TWA	10 mg/m3 700 mg/m3	Total	
TWA	150 ppm 1800 mg/m3 1000 ppm		
o biological exposure limits noted fo	• •		
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.			
		(or goggles).	
	, 5 : : : : : : : : : : : : : : : : : :	· 3-33/	
Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.			
ear suitable protective clothing.			
If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.			
ear appropriate thermal protective			
Ch. Ch.	TWA Description biological exposure limits noted for pool general ventilation (typically 10 rould be matched to conditions. If an other engineering controls to maint exposure limits have not been establish as personal protective equipment are shield is recommended. Wear supplier that the protective clothing is permissible levels are exceeded user-supplied respirator.	TWA 700 mg/m3 150 ppm TWA 1800 mg/m3 1000 ppm biological exposure limits noted for the ingredient(s). cod general ventilation (typically 10 air changes per hour) should be matched to conditions. If applicable, use process enclosure other engineering controls to maintain airborne levels below recorreposure limits have not been established, maintain airborne levels that as personal protective equipment ace shield is recommended. Wear safety glasses with side shields the ear appropriate chemical resistant gloves. Suitable gloves can be applier. ear suitable protective clothing. permissible levels are exceeded use NIOSH mechanical filter / orger-supplied respirator.	

clothing and protective equipment to remove contaminants.

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

9. Physical and chemical properties

Appearance

General hygiene

considerations

Gas. **Physical state** Aerosol. **Form**

ColorNot available.OdorNot available.Odor thresholdNot available.pHNot available.

Melting point/freezing point Not available.

Initial boiling point and boiling

-47.2 °F (-44 °C) estimated

range

Flash point -2.2 °F (-19.0 °C) estimated

Evaporation rate > 1 BuAc estimated

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1.7 % estimated Explosive limit - upper (%) 10.9 % estimated

Vapor pressure 40 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Heat of combustion (NFPA 21 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Specific gravity 0.81 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product name: 17z SEYMR ORNG FLRSCNT MRKNG PNT 20-657

Product #: 1000011638 Version #: 01 Issue date: 04-20-2017

Components	Species	Test Results			
Butane (CAS 106-9)	7-8)				
<u>Acute</u>					
Inhalation					
LC50	Mouse	1237 mg/l, 120 Minutes			
		52 %, 120 Minutes			
	Rat	1355 mg/l			
Isobutyl Acetate (CA	AS 110-19-0)				
<u>Acute</u>					
Dermal	D.II.	47400			
LD50	Rabbit	> 17400 mg/kg, 24 Hours			
Inhalation		> 20 mag/l/ C. Havira			
LC50	Rat	> 30 mg/l, 6 Hours			
		> 23.4 mg/l, 4 Hours			
Oral LD50	Det	42.442 maille			
	Rat	13413 mg/kg			
Propane (CAS 74-98	8-6)				
<u>Acute</u> Inhalation					
LC50	Mouse	1237 mg/l, 120 Minutes			
		52 %, 120 Minutes			
	Rat	1355 mg/l			
	Nat	658 mg/l/4h			
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)					
Acute	etroleum), light aliph. (CAS 64742-69-6)				
<u>Acute</u> Dermal					
LD50	Rabbit	> 1900 mg/kg, 24 Hours			
Inhalation		5 6			
LC50	Rat	> 5000 mg/m3, 4 Hours			
		> 4980 mg/m3			
		> 4980 mg/m3, 4 Hours			
		> 4.96 mg/l, 4 Hours			
Oral		3,			
LD50	Rat	4820 mg/kg			
	product may be based on additional componer				

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

siligle exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Aquatic

Algae IC50 Algae 4700 mg/L, 72 Hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Isobutyl Acetate 1.78 Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

^{*} Estimates for product may be based on additional component data not shown.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN proper shipping name Transport hazard class(es)

UN1950 AEROSOLS

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

LTD QTY Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Isobutyl Acetate (CAS 110-19-0)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Nο

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Listed.

(a))

Butane (CAS 106-97-8)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Calcium Carbonate (CAS 1317-65-3) Isobutyl Acetate (CAS 110-19-0)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Calcium Carbonate (CAS 1317-65-3) Isobutyl Acetate (CAS 110-19-0)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Calcium Carbonate (CAS 1317-65-3) Isobutyl Acetate (CAS 110-19-0)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Isobutyl Acetate (CAS 110-19-0)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(a) or region

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-20-2017

Version # 01

Disclaimer We cannot anticipate all conditions under which this information and its product, or the products of

other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Alternate Trade Names

Product name: 17z SEYMR ORNG FLRSCNT MRKNG PNT 20-657 Product #: 1000011638 Version #: 01 Issue date: 04-20-2017 On inventory (vec/ne)*

Yes